



Artikel-Nr. Stoxxparts	Variante	d1 mm	d2 mm	d3 mm	d4 mm	l1 mm	l2 mm	l3 mm	k mm	SW mm	Federdruck (Anfang) N	Federdruck (Ende) N
05000748001	mit Rastsperre	6	35	M12x1.5	22.8	6	12	49.8	29	14	20	36
05000748002	mit Rastsperre	8	35	M16x1.5	22.8	8	12	54.3	29	14	22	32
05000748003	ohne Rastsperre	6	35	M12x1.5	22.8	6	12	49.8	29	14	20	36
05000748004	ohne Rastsperre	8	35	M16x1.5	22.8	8	12	54.3	29	14	22	32

Edelstahl Druckfeder 1.4571, nichtrostend
 Edelstahlausführung 1.4401, Raststift einsatzgehärtet, nichtrostend
 Dichtungen blau, FDA- konform, temperaturbeständig -25°C bis +110°C
 - H-NBR Dichtring, Härte 85±5 Shore A
 - TPU Abstreifer, Härte 95±5 Shore A



tolerance DIN2768-mk

Status	Änderungen	Datum	Name
Gezeichnet		22.02.2021	Dennis Bruder
Kontrolliert			
Norm			

Edelstahlrastbolzen, Knopfseite in Hygienic Design

REVISION HISTORY

Rev.	Änderungstext	Änderungsdatum	Änderungsstamm	Gen.

05000748000

1

A3

weight -

scale 1:1