



Artikel-Nr. STOXXparts	Abmessungen											für Bolzen d 6	für Schrauben d 6	Belastbarkeit bei statischer Belastung max.	Drehmoment für Schraubver- bindungen max.	Gewicht
	d ₁ H13	d ₂ H13	d ₃	d ₄	d ₅	h ₁	h ₂	h ₃	h ₄		r ₁					
									mit Kegel- pfanne Form D ~	mit Kegel- pfanne Form G ~		[mm]	[mm]	[KN]	[Nm]	[g]
17000108001	6.4	-	12	-	-	0.7	2.3	-	4.2	5.4	9	6	M6	9	10 ¹⁾	1
17000108002	8.4	-	17	-	-	0.6	3.2	-	5.6	7.1	12	8	M8	17	25 ¹⁾	2.8
17000108003	10.5	-	21	-	-	0.8	4	-	6.5	7.3	15	10	M10	26	46 ¹⁾	5.3
17000108004	13	-	24	-	-	1.1	4.6	-	8	9	17	12	M12	38	82 ¹⁾	7.6
17000108005	15	-	28	-	-	1.4	5	-	8.5	9.5	22	14	M14	53	130 ¹⁾	12
17000108006	17	-	30	-	-	1.3	5.3	-	9.6	10.4	22	16	M16	73	206 ¹⁾	13
17000108007	21	-	36	-	-	2	6.3	-	11.7	12.2	27	20	M20	117	407 ¹⁾	23
17000108008	23	-	40	-	-	2.5	7.6	-	13.5	-	29.5	22	M22	146	542 ¹⁾	34
17000108009	25	-	44	-	-	2.4	8.2	-	15.2	15.7	32	24	M24	168	698 ¹⁾	45
17000108010	28	-	50	-	-	3.3	10.2	-	17	-	36	27	M27	221	1021 ¹⁾	74
17000108011	31	-	56	-	-	3.6	11.2	-	19.2	19.7	41	30	M30	269	1355 ¹⁾	101
17000108012	34	-	62	-	-	4.4	13	-	21.8	-	45	33	M33	326 ³⁾	1969 ¹⁾	150
17000108013	37	-	68	-	-	4.6	14	-	23.5	-	50	36	M36	394	2372 ¹⁾	190
17000108014	40	-	75	-	-	5.6	16	-	26.8	-	54	39	M39	460 ³⁾	3276 ¹⁾	218
17000108015	43	-	78	-	-	6.5	17	-	29	-	58	42	M42	542	3802 ¹⁾	310
17000108016	50	-	92	-	-	8	21	-	35.5	-	67	48	M48	714	5730 ¹⁾	540
17000108017	54	-	96	-	-	9.3	22	-	38.3	-	72	52	M52	832 ³⁾	7876 ^{3) 1)}	620
17000108018	58	-	103	-	-	9.8	23	-	39.3	-	79	56	M56	960 ³⁾	9793 ^{3) 1)}	760
17000108019	62	-	112	-	-	11	25	-	43.6	-	86	60	M60	1122 ³⁾	12219 ^{3) 1)}	990
17000108020	66	-	120	-	-	12	27	-	46.6	-	93	64	M64	1269 ³⁾	14762 ^{3) 1)}	1220

STOXXparts
...der Normteile

Gezeichnet	Datum	Name
Kontroll	04.05.2020	Philipp Joos
Norm		
Status	Änderungen	Datum
		Name

tolerance DIN2768-mk

Kugelscheiben, Kegelpfannen,
Kugelscheiben aus Einsatzstahl, Form C

17000108000

1
A3

weight N/A

scale 1:1

Erstfreigabe	05.05.2020		PJ
Rev.	Änderungstext	Änderungsdatum	Änderungsstamm
			Gen.