

Highlights:

- Highflex™ solid & flexible jacket
- 2.5 mm² (13 AWG) thin and dense stranded conductors
- 8 mm (Ø) outer diameter

Product information:

The PLS225 is a high quality loudspeaker cable consisting of two 2.5 mm² (13 AWG) conductors composed with 224 copper strands of 0.12 mm thickness. The combination of thin and dense strands with high purity copper and the flexible and solid PVC outer jacket makes it the perfect cable for various kinds of applications. The smooth outer jacket provides great ease of installation for fixed systems while having perfect rolling & unrolling performance for highly demanding mobile applications.



Inner Conductors:



Usage:

RENTAL

Physical Characteristics:

Inner conductor	Insulation	Material	PVC 3.2 mm (Ø)
		Colours	Red / Blue
Outer jacket	Material		PVC 8 mm (Ø)
		Colours	Black
Type of cable	2-core loudspeaker cable		
Inner conductor	Material	BC 224 x 0.12 mm (Ø) (OFC)	
	Section	2.5 mm ²	
	American Wire Gauge	13 AWG	
	Number of conductors	2	

Mechanical Characteristics:

Temperature range	Fixed installation	- 20 °C till + 70 °C
	Flexible installation	- 5 °C till + 70 °C
Bending radius	Fixed installation	5 x outer diameter
	Flexible installation	10 x outer diameter

Electrical Characteristics:

Lead resistance	0.8 Ω / 100 m
-----------------	---------------

Cross sections:

