

Highlights:

- Stores up to 18 units of 19" Equipment
- Integrated ventilation grid on top
- 50 mm Wheels + leveling feet included
- Removable sides for easy installing & cabling
- Punched square holes for use with snap-in cage nuts
- Front and rear in depth adjustable 19" profiles (max 740 mm)
- Reversible door position
- Mesh perforation with hexagonal pattern
- Swing handle with cylinder lock



The SPR818GG is a professional 19" rack compliant to the ANSI/EIA RS-310D, DIN41491 and IEC60297 standards. A cold rolled steel 2 mm thick frame and 1,2 mm thick plates provides a solid and stable construction making it suitable for heavy equipment, storing up to 18 units inside. The SPR818GG comes fully assembled including 50 mm wheels for easy moving and adjustable feet for fixing and leveling once correctly positioned. The 19" mounting profile with punched square holes for use with snap-in cage nuts in combination with the printed unit measurement indicators ensure an easy fitting of the equipment. Adjustable 19 " profiles provide great flexibility for installing equipment depending on its depth. Both front and rear doors are fitted with a standard keylock.

The SPR818GG comes with 2 perforated steel grill doors (front and rear). The mesh perforation with hexagonal pattern provides an optimal air flow through the cabinet. The swing handle with cylinder lock safely locks the equipment inside.

Product Features:

Unit height		18 HE
Colours		Black (RAL9004)
Max. usable depth		740 mm
Wheel	Diameter	50 mm
Dimensions		600 x 918 (988) x 800 mm (W x H (incl. feet) x D)
Static load capacity (adjustable feet)		800 kg
Dynamic load capacity (transport castors)		400 kg
Weight		59 kg
Accessories	Included	4 x Key for sidepanel lock
		1 x Allen key
		4 x Levelling feet
		4 x Key for front/back door
	Optional	20 x KS600
		20 x KM600
		KS600 - M6 x 16 mm bolt DIN7985 Black
		KM600 - M6 Cage nuts

Variants:

- SPR818GG/B - Black version - Grill front & rear door