

PI PRO: Dual-Mono Power Amplifier



145 mm



Features

- 150W per channel.
- Class A/B operation.
- Hand built in the UK.
- True dual mono design.
- Balanced and unbalanced inputs.
- Amplifier link output.
- 3U 19" rack mount chassis.
- Front panel 'standby' button.
- 6 year warranty.

Specifications

- Output Power :** 150W (8 Ω , 1kHz, continuous. avg., both channels driven)
- Input Sensitivity :** 2V RMS (ref. 150W out)
- Input Impedance:** 10k Ω /leg
- Frequency Response :** <2Hz – >400kHz (-3dB)
- Signal to Noise Ratio :** >115dB (IEC 'A')
- Crosstalk :** >100dB (10Hz – 20kHz)
- THD :** >0.002%/-95dB (8 Ω , 1kHz, -1dB below full Power)
- Damping Factor :** >400 (8 Ω)
- Dimensions (HxWxD) :** 145x483x366mm (3U tall with feet removed)
- Weight :** 18kg/39.6lbs

ATC reserves the right to vary products and specifications without prior notice.



Loudspeaker Technology Ltd

Gypsy Lane, Aston Down, Stroud, Gloucestershire GL6 8HR United Kingdom

Telephone 01285 760561 Fax 01285 760683

Email info@atc.gb.net Website www.atcloudspeakers.co.uk