



PDM200

Paging microphone

Product information:

The PDM200 paging microphone is a polyvalent dynamic gooseneck microphone, mounted on a solid, very stable base and fitted with a three function switch with functions: Permanently ON / Momentary ON / OFF. It is equipped with a switch contact and integrated RC network for use with chime modules. By means of the integrated switch contact and RC network, the PDM200 can activate the chime module of AUDAC COM12/24 or many other public address amplifiers. Its suitable for announcements in all different kinds of environments, ranging from small retail stores and offices to warehouses, large public buildings or big office buildings. A connection cable with a length of 1.5 meter, fitted with a 3-pin XLR connector and connection wires for the chime contacts is attached.

Applications:

- Corporate spaces
- Retail



System specifications:

Microphone	Type	Dynamic
Frequency	Response (± 3 dB)	80 Hz - 12 kHz
Sensitivity (1W/1m)		-70 dB
Impedance	Microphone input	600 Ω
Connectors		3-pin XLR + 3 x Chime conductors
Polar Pattern		Cardioid

Product Features:

Dimensions	110 x 365 x 160 mm (W x H x D)
Weight	0.860 kg
Connection cable length	1.5 m
Colours	Black

Shipping & Ordering:

Packaging	Cardboard box
Shipping weight & volume	1.020 kg - 0.0065 Cbm