

Double section 19" wall mountable rack - 6 units - 550mm depth

Highlights:

- Stores up to 6 units of 19" Equipment
- Integrated ventilation grid on top
- in depth adjustable 19" profiles (max 510 mm)
- Loading capacity of 30 kg
- Tempered glass door with keylock
- Double section allowing easy access to rear side of equipment
- Double lock connecting front and rear section
- Reversible door position



Product information:

The HPR506 is a professional 19" double section wall rack cabinet which complies to ANSI/EIA RS-310D, DIN41491 and IEC60297 standards. It ensures maximum installation, connectivity and maintenance ease storing up to 6 units of 19" equipment. The solid construction made of an 1.5 mm thick steel frame and 1.2 mm thick plates is finished with a black (RAL9004) fine structured powder coating. It provides a stable and secure installation while the double section structure allows easy access to the rear side of the equipment. The tempered smokey glass front door is reversible and secured with a key lock which keeps the equipment accessible for authorized persons only. Other present features are removable sides and in depth adjustable 19" profiles with unit measurement indicators and punched square holes for use with snap-in cage nuts.

Product Features:

| | | |
|-------------------|----------|---------------------------------------|
| Dimensions | | 600 x 368 x 550 mm (W x H x D) |
| Unit height | | 6 HE |
| Max. usable depth | | 510 mm |
| Max. load | | 30 kg |
| Colours | | Black (RAL9004) |
| Weight | | 22.2 kg |
| Accessories | Included | 1 x WPR45LR |
| | | 2 x key for front door |
| | | 4 x Key for sidepanel lock |
| | | 10 x Cage nuts + screws |
| | | 1 x Allen key |
| | Optional | WPR45FS - Fixed shelf |
| | | WPR45LR - L-Rail pair |
| | | WPR10RF - Roof fan 120x120 mm |
| | | SPR10DC - Dust cover brush |
| | | KM600 - M6 Cage nuts |
| | | KS600 - M6 x 16 mm bolt DIN7985 Black |

Architects' and Engineers' Specifications:

The rack shall have the following dimensions: height 368 mm, depth 550 mm, width 600 mm, have a weight of 22,2 kg and hold up to 6 units. It shall comply with ANSI/EIA RS-310D, DIN41491 and IEC60297 standards and have a double section structure which provides maximum installation, connectivity and maintenance ease. The wall part shall be separable from the rack which allows pre loading of the rack and mounting of the panel without the rack attached. The frame of the rack shall be constructed out of cold rolled steel of 1.5 mm thick while for the other parts a thickness of 1.2 mm shall be used. These parts shall have a textured black (RAL9004) powder coating. The mounting profile shall be adjustable in depth and have printed unit measurement indicators. The rack shall include a tempered smokey grey glass door which is reversible in position and equipped with a standard wing knob key lock. The sides of the rack shall be removable and the top shall have a ventilation grid.

