



# KYRA6

Design column speaker 6 x 2"

## Highlights:

---

- Multi-tapping 100V line transformer
- Multi-functional wall bracket allowing swiveling and down-tilting
- Slimline aluminum design
- 6 x 2" high-quality broadband speakers

## Product information:

---

The KYRA column speakers range is the elegant result of research in the field of phased array acoustics. The selection of the highest quality materials including aluminum cone 2" drivers guarantee an extraordinary detail and clarity for music and speech, which is uncommon for any kind of column speaker available from the market. It makes them perfectly lend themselves to a wide variety of applications in acoustic difficult environments such as churches, auditoria, presentation and meeting rooms where audibility and intelligibility of music and speech have the highest importance.

They are housed in slim and elegant constructed enclosures made out of aluminum materials and finished with finely perforated grilles. An included mounting bracket with minimum distance to the wall allows swivelling and down-tilting for perfect directional placement.


The KYRA6 design column speaker consists of 6 x 2" high-quality aluminum cone full-range drivers, delivering extraordinary clarity and detailed sound. The overall continuous power handling reaches 60 Watt and the beamwidth of 170° x 45° makes it the perfect match for acoustically difficult venues, reducing echo and microphone feedback which optimizes the speech intelligibility in reverberant venues.

A multi-tapping line transformer allows it to be connected to 70V/100V public address systems with different power taps for 20W, 10W and 5W and/or low impedance (12Ω) systems.

## Applications:

---

- Education
- Public facilities
- Corporate spaces
- Houses of worship
- Events



## Impedance:

---

12 Ohm

## Voltage:

---

## System specifications:

---

Speaker type		Broadband column
Max. Power		120 W
RMS Power		60 W
Outputs	Impedance	12 $\Omega$
Line Transformer Tappings	1	20 W / 500 $\Omega$
		10 W / 1000 $\Omega$
		5 W / 2000 $\Omega$
Sensitivity (1W/1m)		90 dB
Sound Pressure (Max. W/1m)		106 dB
Dispersion	Horizontal	170°
	Vertical	45° off axis
Frequency	Range (-10 dB)	120 Hz - 20 kHz
Drivers		6 x 2"

## Product Features:

---

Dimensions		70 x 546 x 101 mm (W x H x D)
Construction		Aluminum
Front finish		Aluminium grill
Colours		Black (KYRA6/B)
		White (KYRA6/W)
Accessories	Included	Wall mounting bracket

## Variants:

---

- KYRA6/B - Black version
- KYRA6/W - White version