

### Highlights:

---

- 24 AWG thin and dense stranded conductors
- 3.8 mm (Ø) outer diameter

### Product information:

---

The BMC224 is a balanced microphone cable composed of two stranded conductors surrounded by Al-Mylar shielding in a flexible but durable PVC outer jacket, making it suitable for a wide variation of installation applications such as rack cabling and pulling through tubes and ducts. It consists of a 24 AWG stranded conductor section with Al-Mylar foil shielding and drain wire. Combined with a strong bond between shielding and jacket, stripping of both jacket and shielding can be done in one action which guarantees the highest installer convenience when terminating with connectors. The highly effective shielding offers excellent immunity against noise and interference caused by external devices.



### Inner Conductors:

---



### Shielding:

---



### Usage:

---

INSTALL

## Physical Characteristics:

Inner conductor	Audio	Insulation	Material	HDPE 1.25 mm (Ø)
	Insulation	Colours		White / Red
Overall shielding	Aluminium foil			Al-mylar, 100% coverage - 25% Overlap
Outer jacket	Material			PVC 3.8 mm (Ø)
	Colours			Black
Type of cable				24 AWG Microphone cable
Inner conductor	Material			BC 7 x 0.20 mm (Ø) (OFC)
	Section			0.22 mm <sup>2</sup>
	American Wire Gauge			24 AWG
	Number of conductors			2
	Conductor twisting			Yes


## Standards & regulations:

RoHS2 compliant	According EU Directive 2011/65/EU
Reach compliant	According EC 1907/2006

## Mechanical Characteristics:

Temperature range	Fixed installation	- 20 °C till + 80 °C
	Flexible installation	- 15 °C till + 60 °C
Bending radius	Fixed installation	8 x outer diameter
	Flexible installation	10 x outer diameter

## Cross sections:



## Electrical Characteristics:

Max. conductor	DC resistance	93 (Ω / Km)
Resistance	Insulation	Min. 100 MΩ / km @ 20° C
Dielectric strength		500 (kV / 1 min. DC)
Rated voltage		300 V

## Variants:

- BMC224/1 - 100 meter
- BMC224/3 - 300 meter