



VEXO112A

12" high-output 2-way active loudspeaker

Highlights:

- Compatible with AUDAC Touch™ 2
- Dante expansion port
- Advanced DSP and loudspeaker management
- DuraCoat™ texture paintwork
- High sound pressure levels with tight driver response
- Compatible with TouchLink™
- Ball impact resistance
- Horizontal and vertical mounting
- User friendly mounting
- 125° inclination
- TouchLink™ supported
- WaveDynamics™ supported

The VEXO series are compact 2-way active loudspeakers and come in 3 different models, each of them with different size and performance meeting the requirements of every application. The VEXO series loudspeakers consist of an active and passive versions. The low frequency transducer, which is made out of high quality materials, is combined with a 1.7" voice coil compression driver, enabling high sound pressure levels and a tight driver response with a rotatable 90° x 70° coverage pattern for a wide range of applications.


Thanks to the unique driver composition, the VEXO112 delivers a clear and natural sound with an RMS power of 400 Watts and a maximum power of 1600 Watt. The frequency range (-10dB) starts from 58Hz up to 20 kHz and the sensitivity (1W/1m) reaches 99 dB while a maximum continuous sound pressure level from 125 dB can be achieved.

The construction of the cabinets is made of 12mm plywood with a polyurethane coating, making it resistant for any impact. The front side of the cabinet is finished with a powder coated steel grill with acoustical foam. A recessed carry handle on the rear side makes carrying easy. Positioning and suspension of the speaker is easily achieved by using the standard 35 mm pole adapter on the bottom and the M10 rigging points. Two speaker connectors provide reliable connections with easy link-through to cabinets.

The optional Clever U bracket allows mounting the high power 2-way cabinet both horizontally and vertically. An inclination of 125° in both directions ensures an optimal positioning. The optional MBK bracket even allows mounting the VEXO series to the ceiling which gives the opportunity to install the loudspeaker cleanly in any environment.

By installing the optional ANI44XT Dante™ audio network interface in the active loudspeaker, the VEXO series can be integrated into any Dante enabled AV network and transfer digital audio with any compatible solution on the market.

The VEXO112A features the unique WaveDynamics™ innovation. Due to this DSP processor, the audio control and processing technology enables any user to effortless control the most advanced acoustic configurations. The integrated DSP allows pre-sets for full-range, satellite and custom configurations and can be loaded via the USB slot on the back



Certification:



of the device. By installing the optional ANI44XT Dante audio network interface in the loudspeaker, the VEXO series can be integrated into any Dante™ enabled AV network and transfer digital audio with any compatible solution on the market.

Applications:

- Education
- Sport facilities
- Clubs
- Concert venues

System specifications:

Speaker type			2-way
Max. Power			1600 W
RMS Power			400 W
Impedance			8 Ω
Sensitivity (1W/1m)			99 dB
Sound Pressure (Max. W/1m)			125 dB
Frequency	Response (± 3 dB)		58 Hz - 20 kHz
Dispersion	Horizontal		90°
	Vertical		70°
Crossover	Type		Passive built-in
Drivers	HF		Compression driver with 1.7" VC and 1" throat
	LF		12" (2.5" VC)
Connectors	Remote control		RJ45
	Input		2 x Combo XLR / 6.3 mm jack
			3-pin Euro Terminal Block (Pitch - 3.81 mm)
			3-Pin terminal block (linkthrough)
			XLR male (linkthrough)
Inputs			USB port
			RJ45 (Ethernet)
Power	Consumption	Standby	3.2 W
		Idle	22.5 W

Impedance:



Product Features:

Dimensions		369 x 610 x 390 mm (W x H x D)	
Weight		23.3 kg	
Finish	Cabinet finishing	Polyurethane coating	
Front finish		Powder coated steel grill with acoustical foam	
Mounting & handling	Rigging points	10 x M10	
Construction		12 mm high-quality plywood	
Mounting & handling	Stand fitting	35 mm pole adapter on bottom	
		Carry handles	On top
Powerdrive mount		Powerdrive type 100 (127 x 70 mm)	
Colours		Black & White	
Accessories	Optional	ANI44XT - Dante™ audio network interface	