

CHAT® 150 BT Speakerphone



The CHAT 150 BT is a group USB and Bluetooth speakerphone that enhances your conferencing for the ultimate in business-class performance.

- > NFC tap-to-pair delivers fast and simple connectivity with mobile devices.
- > Sleek and elegant design with touch controls complements professional office aesthetics.
- > Advanced Noise Cancellation, full-duplex Distributed Echo Cancellation®, and Automatic Level Control algorithms deliver highly intelligible, natural, crystal-clear audio.
- > Powerful steerable mic array technology enhances audio pickup at greater distances from the speakerphone.
- > With ClearOne Audio Intelligence™, the CHAT 150 BT speakerphone is unsurpassed in the industry for tabletop conferencing.

APPLICATIONS

- Cloud-based Collaboration
- Cloud-based Audio Conferencing
- Bluetooth Audio Conferencing

WORKSPACES

- Home Offices
- Executive Offices
- Small and mid-sized meeting rooms



The Bluetooth audio bridging feature enables callers from Bluetooth-enabled mobile devices and desk phones to be wirelessly join the call.

COMPATIBLE WITH



Enhance Your Cloud Collaboration

Compatible with popular applications such as Microsoft® Teams, Zoom™, WebEx™, Google® Meet™, and many more.

It's All About the Architecture!®

CHAT® 150 BT Speakerphone

CHAT 150 BT Components




CHAT 150 Unit



USB 2.0 Connection Cable

CHAT 150 BT



CHAT® 150 BT Speakerphone

SYSTEM REQUIREMENTS

- Microsoft Windows® 10 and higher; MAC OS™

CONNECTIONS

- USB: Compatible with USB 2.0 and above, type: Type C receptacle
- Keyed: RJ-45 (8-conductor) - for future use

AUDIO

- Speaker
 - Bandwidth: 190 Hz – 20 kHz
 - Maximum output level: 85 dB SPL @ 1 ft (0.30 meter)
- Microphone(s)
 - Bandwidth: 50 Hz – 7.75 kHz

SUPPORTED BLUETOOTH PROFILES

- RF Radio:
 - Qualified for Bluetooth v5.0 Specification: – HFP 1.7, HSP 1.2, A2DP 1.3, SPP 1.2, AVRCP 1.6, and PBAP 1.2 – Bluetooth classic (BR/EDR)
 - Frequency Spectrum: 2.402 GHz to 2.480 GHz
 - Receive Sensitivity: –90 dBm (2 Mbps EDR, at 0.01% BER)

NFC TAG

- Tap to Bluetooth pair
- Chip (NTAG213)
- Antenna Size (21 mm)
- Memory 180 bytes
- Characters 130

POWER

- USB
 - 5 VDC @ 500 mA maximum
- External
 - 100 - 240 VAC input, 9 VDC @ 560 mA output

CONTROLS

- Volume up
- Volume down
- Microphone mute
- Bluetooth pair

ENVIRONMENTAL

- Operating temperature: 41 - 104 °F (5 - 40 °C)

PROCESSING

- Full duplex
- Distributed Echo Cancellation (D. E. C.)
- Noise Cancellation (NC)
- Automatic Level Control (ALC)
- First Mic Priority

MECHANICAL

- Dimensions (W x D x H): 7.4 x 7.4 x 1.8 in (188 x 188 x 46 mm)
- Weight: 1.17 lbs (0.53 kg)

PART NUMBERS

- 910-156-500 CHAT 150 BT

SALES AND INQUIRIES**Headquarters**

5225 Wiley Post Way
Suite 500
Salt Lake City, UT 84116

US & Canada

Tel: 801.975.7200

International

Tel: +1.801.975.7200

Sales

Tel: 801.975.7200
sales@clearone.com

Tech Support

Tel: 801.974.3760
audiotechsupport@clearone.com