


Highlights:

- Flexible PVC jacket
- Stranded conductors
- H05VV-F

Product information:

The PC3G25 are high quality standard H05VV-F power cables for indoor and outdoor, fixed or mobile use. The cables are made of 3 PVC insulated conductors with an inner section of 3 x 2,5mm². Packed in a highly flexible PVC outer jacket of 9 mm, this offers you a cable that can be used in a wide variety of applications, even in damp spaces.



Inner Conductors:



Usage:

MOBILE

Physical Characteristics:

Inner conductor	Insulation	Material	PVC 3.5 mm (Ø)
		Colours	Blue / Brown / Yellow & Green
Outer jacket	Material		Flexible PVC 9 mm (Ø)
	Colours		Black
Type of cable			3G2.5 PVC power cable
Inner conductor	Material		BC 48 x 0.254 mm (Ø) (OFC)
	Section		2.5 mm²
	American Wire Gauge		13 AWG
	Number of conductors		3

Mechanical Characteristics:

Temperature range	Fixed installation	- 40 °C till + 80 °C
	Flexible installation	- 25 °C till + 60 °C
Bending radius	Fixed installation	8 x outer diameter
	Flexible installation	8 x outer diameter

Electrical Characteristics:

Lead resistance	0.66 Ω / 100 m
Max. current	20 Amp
Max. operation voltage	300 V